

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Rhepanol-Kontaktkleber 50 S

UFI: GE6Y-RH4H-M008-GAMJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesives

Uses advised against

Only use for the intended purpose.

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	FDT Flachdach Technologie GmbH	
Street:	Eisenbahnstraße 6-8	
Place:	D-68199 Mannheim	
Telephone:	+49 (621) 8504100	Telefax: +49 (621) 8504200
e-mail:	kundenservice@fdt.de	
Contact person:	Fachkraft für Arbeitssicherheit	Telephone: +49 (621) 8504303
e-mail:	gefahrstoffe@fdt.de	
Internet:	http://www.fdt.de	
Responsible Department:	Arbeitssicherheit und Umweltschutz	

1.4. Emergency telephone number:

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department or the NHS enquiry service.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane acetone; propan-2-one; propanone

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 2 of 11

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
115-10-6	Dimethyleter (*drivgas)			50-100 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1; H220			
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			25-<50 %
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
67-64-1	acetone; propan-2-one; propanone			5-<10 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Further Information

*The substance is added to the mixture as a propellant. According to CLP Annex 1.1.3.7, the propellant is not taken into account in the calculation of the hazard classification of the total mixture.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of troubles or persistent symptoms, consult an doctor/physician.

Remove persons from danger area and lie them down. Never orally infuse something to an unconscious person. No special first aid measures necessary. A vomiting, supine person must be brought into recovery position.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of irregular breathing or respiratory arrest, perform artificial respiration.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 3 of 11

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Subsequently wash off with: Polyethylene glykol 400. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth, spit liquid again. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

After skin contact: Irritation and reddening.
May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Sand. Extinguishing powder. Water spray. Fight larger fires with water spray jet or alcohol-resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to harmful gases and vapours.

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Pick up dry. Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.
Do not rinse with water or watery detergents.

6.4. Reference to other sections

Safe handling: see section 7
Personal precautions: refer to section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Handle and open container with care.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 4 of 11

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store only in original container. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

adhesives

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			
	Consumer DNEL, long-term	oral		1301 mg/kg bw/day
	Consumer DNEL, long-term	dermal		1377 mg/kg bw/day
	Worker DNEL, long-term	dermal		13964 mg/kg bw/day
	Consumer DNEL, long-term	inhalation		1131 mg/m ³
	Worker DNEL, long-term	inhalation		5306 mg/m ³
67-64-1	acetone; propan-2-one; propanone			
	Consumer DNEL, long-term	oral		62 mg/kg bw/day
	Consumer DNEL, long-term	dermal		62 mg/kg bw/day
	Worker DNEL, long-term	dermal		186 mg/kg bw/day
	Consumer DNEL, long-term	inhalation		200 mg/m ³
	Worker DNEL, acute	inhalation		2420 mg/m ³
	Worker DNEL, long-term	inhalation		1210 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 5 of 11

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Soil		29,5 mg/kg
Marine sediment		3,04 mg/kg
Freshwater sediment		30,4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l

8.2. Exposure controls

Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.
Avoid skin, eye and clothing contact. After contact with skin, wash immediately with plenty of water and soap or a suitable cleaning agent.

Eye/face protection

Tightly fitting safety glasses with side shields.

Hand protection

Protect skin by using skin protective cream. Wear suitable gloves.
When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.
The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Suitable material: Butyl rubber.
Thickness of glove material: 0,7 mm
penetration time (maximum wearing period): 8h

Respiratory protection

Use protective filter mask in case of short-term and low exposure; in case of intense or longer exposure, use respiratory protection device operating independently from circulating air.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: lime-green
Odour: characteristic

pH-Value: not determined

Changes in the physical state

Melting point: not determined
Initial boiling point and boiling range: 56 °C
Flash point: -20 °C

Flammability

Gas: not determined

Explosive properties

not determined

Lower explosion limits: 1,2 vol. %

Test method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontakkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 6 of 11

Upper explosion limits:	13,0 vol. %
Ignition temperature:	247 °C
Auto-ignition temperature	
Gas:	not determined
Decomposition temperature:	not determined
Oxidizing properties	
not determined	
Vapour pressure: (at 20 °C)	247 hPa
Density (at 20 °C):	0,88 g/cm ³ DIN 53217/2
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Partition coefficient:	not determined
Viscosity / dynamic: (at 20 °C)	3000 mPa·s ISO 2555
Viscosity / kinematic:	not determined
Vapour density:	not determined
Solvent content:	not determined

9.2. Other information

No further information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reactivity under regular conditions.

10.2. Chemical stability

The product is stable under regular conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 7 of 11

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
115-10-6	Dimetyleter (*drivgas)					
	inhalation (4 h) vapour	LC50	308 mg/l	Rat		
67-64-1	acetone; propan-2-one; propanone					
	oral	LD50 mg/kg	5800	Rat	OECD 401	
	dermal	LD50 mg/kg	>15800	Rat		
	inhalation (4 h) vapour	LC50	76 mg/l	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone						
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna		
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum		

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 8 of 11

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Disposal according to official regulations.

Consult the local waste disposal expert about waste disposal. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3



Classification code:	F1
Special Provisions:	640H
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 9 of 11



Classification code: F1
Special Provisions: 640H
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: Nein
Special Provisions: 223, 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

No special precautions known.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50 S

Revision date: 23.02.2021

Product code: FDT-003

Page 11 of 11

LC: Lethal concentration
 LD: Lethal dose
 log Kow: Octanol/water partition coefficient
 MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships
 OECD: Organisation for Economic Co-operation and Development
 PBT: Persistent, bio-cumulative, toxic
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail
 TRGS: Technische Regeln für Gefahrstoffe
 UN: United Nations
 VOC: Volatile Organic Compounds
 vPvB: very persistent and very bio-cumulative
 WGK: German Water Hazard Class
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 DNEL: Derived No Effect Level
 PNEC: Predicted No Effect Concentration
 TLV: Threshold Limiting Value
 STOT: Specific Target Organ Toxicity
 AwSV: Ordinance on Installations for Handling Substances Hazardous to Water

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:

assesio AG, Ottostraße 1, 63741, Aschaffenburg, Germany
 Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@assesio.eu, www.assesio.eu

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)