

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Rhepanol-Kontaktkleber 50

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesives

Uses advised against

Only use for the intended purpose.

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	FDT Flachdach Technologie GmbH & Co. KG	
Street:	Eisenbahnstraße 6-8	
Place:	D-68199 Mannheim	
Telephone:	+49 (621) 8504100	Telefax: +49 (621) 8504200
e-mail:	kundenservice@fdt.de	
Contact person:	Marco Anderer	Telephone: +49 (621) 8504563
e-mail:	marco.anderer@fdt.de	
Internet:	http://www.fdt.de	
Responsible Department:	Arbeitssicherheit und Umweltschutz	

1.4. Emergency telephone

number: Poison Control Center (Mayence, GER)

+49 (0)6131-19240 (24h - de, en)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components which must be listed on the label

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
cyclohexane

acetone; propan-2-one; propanone

n-hexane

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontakkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 2 of 11

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P501	Dispose of contents/container in accordance with national disposal regulations.

2.3. Other hazards

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			25-<50 %
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
110-82-7	cyclohexane			2,5-<10 %
	203-806-2	601-017-00-1	01-2119463273-41	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			
67-64-1	acetone; propan-2-one; propanone			2,5-<10 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
110-54-3	n-hexane			0,5-<1,5 %
	203-777-6	601-037-00-0	01-2119480412-44	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of troubles or persistent symptoms, consult an doctor/physician.

Remove persons from danger area and lie them down. Never orally infuse something to an unconscious person. No special first aid measures necessary. A vomiting, supine person must be brought into recovery position.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 3 of 11

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.
In case of irregular breathing or respiratory arrest, perform artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Subsequently wash off with: Polyethylene glykol 400. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth, spit liquid again. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

After skin contact: Irritation and reddening.
May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Sand. Extinguishing powder. Water spray. Fight larger fires with water spray jet or alcohol-resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to harmful gases and vapours.

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Pick up dry. Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.
Do not rinse with water or watery detergents.

6.4. Reference to other sections

Safe handling: see section 7
Personal precautions: refer to section 8.
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 4 of 11

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations. Handle and open container with care.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store only in original container. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

adhesives

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			
	Consumer DNEL, long-term	oral		1301 mg/kg bw/day
	Consumer DNEL, long-term	dermal		1377 mg/kg bw/day
	Worker DNEL, long-term	dermal		13964 mg/kg bw/day
	Consumer DNEL, long-term	inhalation		1131 mg/m ³
	Worker DNEL, long-term	inhalation		5306 mg/m ³
67-64-1	acetone; propan-2-one; propanone			
	Consumer DNEL, long-term	oral		62 mg/kg bw/day
	Consumer DNEL, long-term	dermal		62 mg/kg bw/day
	Worker DNEL, long-term	dermal		186 mg/kg bw/day
	Consumer DNEL, long-term	inhalation		200 mg/m ³
	Worker DNEL, acute	inhalation		2420 mg/m ³
	Worker DNEL, long-term	inhalation		1210 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 5 of 11

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Soil		29,5 mg/kg
Marine sediment		3,04 mg/kg
Freshwater sediment		30,4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l

8.2. Exposure controls

Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Avoid skin, eye and clothing contact. After contact with skin, wash immediately with plenty of water and soap or a suitable cleaning agent.

Eye/face protection

Tightly fitting safety glasses with side shields.

Hand protection

Protect skin by using skin protective cream. Wear suitable gloves. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Skin protection

Full cover clothing covering arms and legs.

Respiratory protection

Use protective filter mask in case of short-term and low exposure; in case of intense or longer exposure, use respiratory protection device operating independently from circulating air.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: lime-green
 Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined
 Initial boiling point and boiling range: 56 °C
 Flash point: -18 °C

Flammability

Gas: not determined

Explosive properties

not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontakkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 6 of 11

Lower explosion limits:	1,2 vol. %
Upper explosion limits:	13,0 vol. %
Ignition temperature:	260 °C
Auto-ignition temperature	
Gas:	not determined
Decomposition temperature:	not determined
Oxidizing properties	
not determined	
Vapour pressure:	247 hPa
(at 20 °C)	
Density (at 20 °C):	0,88 g/cm ³ DIN 53217/2
Water solubility:	insoluble
Partition coefficient:	not determined
Viscosity / dynamic:	3000 mPa·s ISO 2555
(at 20 °C)	
Viscosity / kinematic:	not determined
Vapour density:	not determined
Solvent content:	not determined

9.2. Other information

No further information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactivity under regular conditions.

10.2. Chemical stability

The product is stable under regular conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 7 of 11

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50	5800 mg/kg	Rat	OECD 401
	dermal	LD50	>15800 mg/kg	Rat	
	inhalative (4 h) vapour	LC50	76 mg/l	Rat	

Irritation and corrosivity

Causes skin irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane), (cyclohexane), (acetone; propan-2-one; propanone), (n-hexane)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna	
	Algae toxicity	NOEC	4740 mg/l	2 d	Selenastrum capricornutum	
110-54-3	n-hexane					
	Acute fish toxicity	LC50	2,5 mg/l	96 h	Pimephales promelas	Geiger et al. 1990

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
110-54-3	n-hexane	3,9

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontakkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 8 of 11

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Disposal according to official regulations.

Consult the local waste disposal expert about waste disposal. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1133
14.2. UN proper shipping name:	Adhesives
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Classification code:	F1
Special Provisions:	640H
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 1133
14.2. UN proper shipping name:	Adhesives
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 9 of 11



Classification code: F1
Special Provisions: 640H
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: Nein
Special Provisions: 223, 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

No special precautions known.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontaktkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 10 of 11

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 49,38%
434,5g/l

Additional information

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable

Regulation (EC) No. 648/2004 (Detergents regulation): not applicable

REGULATION (EC) No 850/2004 on persistent organic pollutants: not applicable

REGULATION (EC) No 689/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of dangerous chemicals: This mix contains no chemicals that are subject to the export notification procedures (annex 1).

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

cyclohexane

acetone; propan-2-one; propanone

n-hexane

SECTION 16: Other information

Changes

Version 1,00 - Creation - 23.05.2014

Version 1,01 - Classification/Labeling according Regulation No.1272/2008 (GHS/CLP) and general revision - 15.06.2015

Version 1,02 - Change and revision of the SDS because of new information / recipe - 03.09.2015

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BImSchV (Fed.Imm.Prot.Act): Directive on the Implementation of the Federal Immission Protection Act

CAS: Chemical Abstracts Service

EC: Effective Concentration

EG: European Community (Europäische Gemeinschaft)

EN: European Norm

IATA: International Air Transport Association

IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in Bulk

ICAO: International Civil Aviation Organization

IMDG: International Maritime Code for Dangerous Goods

CLP: Classification, Labeling, Packaging

IUCLID: International Uniform Chemical Information Database

LC: Lethal concentration

LD: Lethal dose

log Kow: Octanol/water partition coefficient

MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Kontakkleber 50

Print date: 15.09.2015

Product code: RCSO-FDT-005

Page 11 of 11

OECD: Organisation for Economic Co-operation and Development
PBT: Persistent, bio-cumulative, toxic
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail
TRGS: Technische Regeln für Gefahrstoffe
VOC: Volatile Organic Compounds
vPvB: very persistent and very bio-cumulative
VwVwS: Administrative Regulation for Water Pollutants
WGK: German Water Hazard Class
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
TLV: Threshold Limiting Value
STOT: Specific Target Organ Toxicity

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:

REACheck Solutions GmbH, Frohsinnstraße 28, 63739 Aschaffenburg, Germany
Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@reacheck.eu,
www.reacheck.eu

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)